

AMX-H110ZH Series

Mini-ITX Standard Barebone with Intel® Kaby Lake/Skylake



Features

- Intel® Desktop Core™ Processor
- 2 x 2.5" SATA HDD
- 2 X PCI or 1 X PCIe(x1) expansion slots
- HDMI x1 ,DP x 1
- COM 1~4: RS-232 COM5 : RS485
- 3 x Intel® I211-AT GbE LAN
- Mirror Box (Raid 1) Ready

SPEC

| | | |
|----------------------------|-----------------------|---|
| System | CPU | Intel® Core™ i7-6700, Quad Core, 8M Cache, 3.4GHz (4.0GHz), 65W Intel® Core™ i5-6500, Quad Core, 6M Cache, 3.2GHz (3.6GHz), 65W Intel® Core™ i3-6100, Dual Core, 3M Cache, 3.7GHz, 47W Intel® Pentium® G4400, Dual Core, 3M Cache, 3.3GHz, 47W |
| | Max. capacity | 2x Dual Channel DDR4 2133MHz max. 32GB |
| Graphic | Controller | Intel® HD Graphics |
| Ethernet | Controller | 3 x Intel® I211-AT GbE LAN Wake on lan supported |
| Audio | Controller | Realtek HD ALC662 5.1 Channel Codec |
| Storage | | 2 x 2.5" HDD/SSD drive bay 1 x M.2 for 2242 SSD |
| Expansion Slot | PCIe or PCI slot | 2 X PCI or 1 X PCIe(x1) |
| I/O Interface | Audio | 1x Line-out, 1x MIC-in |
| | USB | 4 x USB 3.0, 2 x USB 2.0, 2 x USB 2.0(Front) |
| | Display Interface | 1 x HDMI 1.4 1 x DP1.2 |
| | Serial Ports | Max 5 x COM (Option) COM 1~4: RS-232 COM5 : RS485 |
| Power Supply | | 250W/300W FlexATX power / Input voltage :100V ~ 240V |
| Environmental | Operating temperature | 0 ~ 45°C |
| | Operating humidity | 10 ~ 95% RH @ 55°C (non-condensing) |
| Mechanical | Physical dimension | 230 x 230 x 205 mm |
| | Weight (Net) | 6KG |
| Certification | EMI /MEC | Compliant with CE, FCC, |
| Software operating support | | Windows 10 (64-bit), Windows 7 (32/64-bit) |

Dimensions

